



INGENIERIA ELECTRONICA APLICADA A LAS VIBRACIONES

José María Mestre No. 26, Col. Miguel Hidalgo 1ª Sección, México, D. F. C. P. 14260
 Tel. +52 55 5606 42 17 Móvil: 55 2083 3466
daniel.paredes@ieav.com.mx

www.ieav.com.mx

VB-8212

Aceleración y Velocidad-Sistema Métrico e Inglés

1. FEATURES

- * Applications for industrial vibration monitoring :
All industrial machinery vibrates. The level of vibration is a useful guide to machine condition. Poor balance, misalignment & looseness of the structure will cause the vibration level increase, it is a sure sign that the maintenance is needed.
- * Professional vibration meter supply with vibration sensor & magnetic base, full set.
- * Velocity measuring range 200 mm/s, 7.87 inch/s.
- * Acceleration measuring range 200 m/s^2 ,656 ft/s^2
- * Metric & Imperial display unit.
- * Frequency range 10 Hz - 1 kHz, sensitivity relative meet ISO 2954.
- * RMS & Peak measurement.
- * Wide frequency range.
- * Data hold button to freeze the desired reading.
- * Memory function to record maximum and minimum reading with recall.
- * Separate vibration probe, easy operation
- * RS 232 computer interface.
- * Optional data acquisition software for data record & datalogger.
- * Super large LCD display.
- * Microcomputer circuit, high performance.
- * Auto shut off saves battery life.
- * Built-in low battery indicator.
- * Heavy duty & compact housing case.
- * Complete set with the hard carrying case.

2. SPECIFICATIONS

Display	61 mm x 34 mm supper large LCD display. 15 mm (0.6") digit size.
Measurement	Velocity, Acceleration RMS value, Peak value, Data hold, Max. & Min. value.
Range	Velocity : 200 mm/ : 0.5 to 199.9 mm/s 7.87 inch/s : 0.02 to 7.87 inch/s Acceleration : 200 m/s^2 : 0.5 to 199.9 m/s^2 656 ft/s^2 : 2 to 656 ft/s^2
Resolution	Velocity : 0.1 mm/s ,0.01 inch/s Acceleration : 0.1 m/s^2 ,1 ft/s^2
Frequency range	10 Hz to 1 KHz * Sensitivity relative during the the frequency range meet ISO 2954

Accuracy	(5 % + 2 d) reading , 160 Hz, 80 Hz. @ 160 Hz, 80 Hz Cal. @ 23 ± 5 °C
Calibration point	Velocity : 50 mm/s (160 Hz) Acceleration : 50 m/s^2 (160 Hz)
Circuit	Exclusive microcomputer circuit.
Data hold	Freeze the desired reading.
Peak measurement	To measure the peak value.
Memory	Maximum & Minimum value.
Power off	Auto shut off, saves battery life, or manual off by push button.
Sampling time	Approx. 1 second.
Data output	RS 232 serial output, isolate.
Operating temperature	0 to 50 °C (32 to 122 °F).
Operating humidity	Less than 80% RH.
Power supply	Alkaline or heavy duty type, DC 9V battery, 006P, MN1604 (PP3) or equivalent.
Power consumption	Approx. DC 6 mA.
Weight	<i>Meter</i> 230 g/0.50 LB <i>Probe with sensing head</i> 165 g/0.36 LB
Dimension	<i>Meter :</i> 180 x 72 x 32 mm (7.1 x 2.8 x 1.3 inch). <i>Vibration probe :</i> Round 36 mm Dia. x 71 mm. <i>Sensing head :</i> 8.9 mm Dia x 42 mm length <i>Cable length :</i> 1.2 meter.
Accessories included	Instruction manual..... 1 PC. Cable with plugs..... 1 PC. Vibration probe..... 1 PC. Sensing head..... 1 PC. Magnetic base..... 1 PC. Carrying Case..... 1 PC.
Optional accessories	* Software (Windows version, data record & data acquisition) SW-U801-WIN * RS232 cable..... UPCB-01 * USB cable..... USB-01

